

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/05/2016

Reviewed on 04/05/2016

1 Identification

- **Product name:** ClearSet Acrylic Liquid
- **Part number:**
171-10000
171-10025, 171-10035
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Allied High Tech Products Inc.
2376 East Pacifica Place
USA-RANCHO DOMINGUEZ, CA 90220
USA
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (310) 635-2466
Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/05/2016

Reviewed on 04/05/2016

Product name: ClearSet Acrylic Liquid

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

methyl methacrylate

N,N-dimethyl-p-toluidine

· **Hazard statements**

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 2

· **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 2

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/05/2016

Reviewed on 04/05/2016

Product name: ClearSet Acrylic Liquid

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous Components:**

80-62-6	methyl methacrylate ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
99-97-8	N,N-dimethyl-p-toluidine ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT RE 2, H373; Flam. Liq. 4, H227; Aquatic Chronic 3, H412	0.1-≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/05/2016

Reviewed on 04/05/2016

Product name: ClearSet Acrylic Liquid

(Contd. of page 3)

- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Do not allow to enter sewers/ surface or ground water.
Prevent seepage into sewage system, workpits and cellars.
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store at temperatures not exceeding 25 °C.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

80-62-6 methyl methacrylate

PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Long-term value: 410 mg/m ³ , 100 ppm
TLV	Short-term value: 410 mg/m ³ , 100 ppm Long-term value: 205 mg/m ³ , 50 ppm
	DSEN

99-97-8 N,N-dimethyl-p-toluidine

WEEL	Long-term value: 0.5 ppm
------	--------------------------

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/05/2016

Reviewed on 04/05/2016

Product name: ClearSet Acrylic Liquid

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:** *Use suitable respiratory protective device when high concentrations are present.*

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Clear

· **Odor:** Acrid

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: -48 °C (-54 °F)

Boiling point/Boiling range: 101 °C (214 °F)

· **Flash point:** 11 °C (52 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 430 °C (806 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/05/2016

Reviewed on 04/05/2016

Product name: ClearSet Acrylic Liquid

(Contd. of page 5)

· Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapor pressure at 20 °C (68 °F): 47 hPa (35 mm Hg)	
· Density at 20 °C (68 °F): 0.94 g/cm ³ (7.844 lbs/gal)	
· Relative density Not determined.	
· Vapor density at 20 °C (68 °F) 3.5	
· Specific gravity: 0.949 (water = 1)	
· Evaporation rate 3.1 (Butyl acetate = 1)	
· Solubility in / Miscibility with Water at 20 °C (68 °F): 1.6 g/l	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
VOC content:	0.0 g/l / 0.00 lb/gl
· Other information No further relevant information available.	

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Danger of polymerization.
- **Conditions to avoid**
Keep away from oxidising agents and acidic substances.
Keep away from heat.
Protect from sunlight.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	165829 mg/kg (rat)
Dermal	LD50	4326 mg/kg
Inhalative	LC50/4 h	16.1 mg/l (rat)

80-62-6 methyl methacrylate

Oral	LD50	7872 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/05/2016

Reviewed on 04/05/2016

Product name: ClearSet Acrylic Liquid

(Contd. of page 6)

Inhalative	LC50/4 h	18 mg/l (rat)	
99-97-8 N,N-dimethyl-p-toluidine			
Oral	LD50	1650 mg/kg (rat)	
Dermal	LD50	300 mg/kg (ATE)	
Inhalative	LC50/4 h	1.4 mg/l (rat)	
<ul style="list-style-type: none"> · Primary chemical irritant effect: · on the skin: Irritant to skin and mucous membranes. · on the eye: No irritating effect. · Sensitization: Sensitization possible through skin contact. · Additional toxicological information: · Carcinogenic categories 			
· IARC (International Agency for Research on Cancer)			
80-62-6	methyl methacrylate		3
· NTP (National Toxicology Program)			
None of the ingredients is listed.			
· OSHA-Ca (Occupational Safety & Health Administration)			
None of the ingredients is listed.			

12 Ecological information

- **Toxicity**

· Aquatic toxicity:	
80-62-6 methyl methacrylate	
EC50 (96 h)	170 mg/l (pseudokirchneriella subcapitata)
EC50 (48 h)	69 mg/l (daphnia)
LC50 (96 h)	79 mg/l (oncorhynchus mykiss)
99-97-8 N,N-dimethyl-p-toluidine	
LC50 (96 h)	46 mg/l (pimephales promelas)

- **Persistence and degradability** Not easily biodegradable
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Contact waste processors for recycling information.

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/05/2016



Reviewed on 04/05/2016

Product name: ClearSet Acrylic Liquid

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA 	<p style="text-align: right;">UN1247</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA 	<p style="text-align: right;">Methyl methacrylate monomer, stabilized METHYL METHACRYLATE MONOMER, STABILIZED</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> · Class · Label 	<p style="text-align: right;">3 Flammable liquids 3</p>
<ul style="list-style-type: none"> · IMDG, IATA 	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> · Class · Label 	<p style="text-align: right;">3 Flammable liquids 3</p>
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	<p style="text-align: right;">II</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	<p style="text-align: right;">No</p>
<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category · Stowage Code 	<p style="text-align: right;">Warning: Flammable liquids 33 F-E,S-D B SW2 Clear of living quarters.</p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	<p style="text-align: right;">Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: · DOT · Quantity limitations 	<p style="text-align: right;">On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) 	<p style="text-align: right;">1L</p>

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/05/2016

Reviewed on 04/05/2016

Product name: ClearSet Acrylic Liquid

(Contd. of page 8)

· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

80-62-6 | methyl methacrylate

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

99-97-8 | N,N-dimethyl-p-toluidine

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

80-62-6 | methyl methacrylate | E, NL

- **TLV (Threshold Limit Value established by ACGIH)**

80-62-6 | methyl methacrylate | A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Contact:** Kim Dermit

- **Date of preparation / last revision** 04/05/2016 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/05/2016

Reviewed on 04/05/2016

Product name: ClearSet Acrylic Liquid

(Contd. of page 9)

IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

US

Safety Data Sheet acc. to OSHA HCS

Printing date 04/04/2016

Reviewed on 04/04/2016

1 Identification

- **Product name:** ClearSet Acrylic Powder
- **Part number:**
171-10000
171-10005, 171-10030
- **Application of the substance / the mixture** Acrylic resin
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Allied High Tech Products Inc.
2376 East Pacifica Place
USA-RANCHO DOMINGUEZ, CA 90220
USA
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (310) 635-2466
Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

- **Classification of the substance or mixture**
The product is not classified according to the Globally Harmonized System (GHS).

- **Label elements**
- **GHS label elements** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2016

Reviewed on 04/04/2016

Product name: ClearSet Acrylic Powder

(Contd. of page 1)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous Components:**

9011-14-7	Methyl methacrylate polymer	Combustible Dust	50-100%
84-66-2	diethyl phthalate		10-<25%

4 First-aid measures

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose of the collected material according to regulations.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2016

Reviewed on 04/04/2016

Product name: ClearSet Acrylic Powder

(Contd. of page 2)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** *No special measures required.*
- **Information about protection against explosions and fires:** *No special measures required.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *Store at temperatures not exceeding 35 °C.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *None.*
- **Specific end use(s)** *No further relevant information available.*

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

9011-14-7 Methyl methacrylate polymer

PEL	Long-term value: 410 mg/m ³
TLV	Long-term value: 205 mg/m ³

84-66-2 diethyl phthalate

REL	Long-term value: 5 mg/m ³
TLV	Long-term value: 5 mg/m ³

- **Additional information:** *The lists that were valid during the creation were used as basis.*

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
- **Breathing equipment:** *Not required.*
- **Protection of hands:**
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** *Not required.*

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
Form: Powder

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2016

Reviewed on 04/04/2016

Product name: ClearSet Acrylic Powder

(Contd. of page 3)

Color:	White
· Odor:	Light
· Odor threshold:	Not determined.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	304 °C (579 °F)
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not applicable.
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Organic solvents:	0.0 %
VOC content:	0.0 g/l / 0.00 lb/gl
Solids content:	100.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
Keep away from oxidising agents and acidic substances.
Temperatures above 240 °C (464 °F)
- **Incompatible materials:** No further relevant information available.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2016

Reviewed on 04/04/2016

Product name: ClearSet Acrylic Powder

(Contd. of page 4)

- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Methacrylate monomers
- **Additional information:** Hazardous decomposition products may form during combustion.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

84-66-2 diethyl phthalate

Oral	LD50	8600 mg/kg (rat)
Dermal	LD50	> 11200 mg/kg (rat)

- **Primary chemical irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
Abrasive skin irritant
Abrasive eye irritant
When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

9011-14-7	Methyl methacrylate polymer	3
-----------	-----------------------------	---

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

84-66-2 diethyl phthalate

EC50 (96 h) (static)	21 mg/l (fresh water algae)
EC50 (48 h) (static)	86 mg/l (daphnia)
LC50 (96 h)	12 mg/l (oncorhynchus mykiss)
	4.29 mg/l (pseudokirchneriella subcapitata)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2016

Reviewed on 04/04/2016

Product name: ClearSet Acrylic Powder

(Contd. of page 5)

- *Danger to drinking water if even small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Contact waste processors for recycling information.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|-----------------|
| · UN-Number | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · DOT, ADN, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · DOT, IMDG, IATA | not regulated |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2016

Reviewed on 04/04/2016

Product name: ClearSet Acrylic Powder

(Contd. of page 6)

· Proposition 65
· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories
· EPA (Environmental Protection Agency)

84-66-2 diethyl phthalate

D

· TLV (Threshold Limit Value established by ACGIH)

84-66-2 diethyl phthalate

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: Kim Dermit

· Date of preparation / last revision 04/04/2016 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit