

Safety Data Sheet acc. to OSHA HCS

Printing date 03/28/2016

Reviewed on 03/28/2016

1 Identification

- **Product name:** Mold Release Spray, Silicone (Hot Mounting)
- **Part number:** 200-10005
- **Application of the substance / the mixture** Releasing agent
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Allied High Tech Products Inc.
2376 East Pacifica Place
USA-RANCHO DOMINGUEZ, CA 90220
USA
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (310) 635-2466
Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS08 Health hazard

Carc. 2	H351	Suspected of causing cancer.
STOT RE 1	H372	Causes damage to the central nervous system through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2016

Reviewed on 03/28/2016

Product name: Mold Release Spray, Silicone (Hot Mounting)

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Stoddard solvent

· **Hazard statements**

Extremely flammable aerosol. Pressurized container: May burst if heated.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not spray on an open flame or other ignition source.

Wear protective gloves.

Wear eye protection / face protection.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 0

Reactivity = 3

· **HMIS-ratings (scale 0 - 4)**



Health = *1

Fire = 0

Reactivity = 3

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2016

Reviewed on 03/28/2016

Product name: Mold Release Spray, Silicone (Hot Mounting)

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous Components:**

74-98-6	propane ⚠ Flam. Gas 1, H220; Press. Gas, H280	10-<25%
8052-41-3	Stoddard solvent ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; Asp. Tox. 1, H304	2.5-<10%
1330-20-7	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	0.1-≤2.5%
100-41-4	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	0.1-≤2.5%

· **Non-hazardous Components:**

90622-56-3	Alkanes, C7-10-iso-	50-100%
	Resin	2.5-<10%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
Headache
Dizziness
Unconsciousness
Breathing difficulty
Disorientation
Nausea
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2016

Reviewed on 03/28/2016

Product name: Mold Release Spray, Silicone (Hot Mounting)

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store at temperatures not exceeding 50 °C.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2016

Reviewed on 03/28/2016

Product name: Mold Release Spray, Silicone (Hot Mounting)

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppm

REL Long-term value: 1800 mg/m³, 1000 ppm

TLV refer to Appendix F in TLVs and BEIs book

8052-41-3 Stoddard solvent

PEL Long-term value: 2900 mg/m³, 500 ppm

REL Long-term value: 350 mg/m³

Ceiling limit value: 1800* mg/m³
*15-min

TLV Long-term value: 525 mg/m³, 100 ppm

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm

Long-term value: 434 mg/m³, 100 ppm

BEI

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 87 mg/m³, 20 ppm

BEI

· **Ingredients with biological limit values:**

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2016

Reviewed on 03/28/2016

Product name: Mold Release Spray, Silicone (Hot Mounting)

(Contd. of page 5)

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Color: Colorless

· **Odor:** Mild

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:**

Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

Lower: Not determined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2016

Reviewed on 03/28/2016

Product name: Mold Release Spray, Silicone (Hot Mounting)

(Contd. of page 6)

Upper:	Not determined.
· Vapor pressure:	2666 hPa (2000 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Specific gravity:	0.712
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	22.5 %
VOC content:	22.5 %
	225.4 g/l / 1.88 lb/gl
Solids content:	73.9 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
 - Keep away from oxidising agents and acidic substances.
 - Keep away from heat.
 - Keep away from open flames. - No smoking.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	273997 mg/kg (rat)
------	------	--------------------

- **Primary chemical irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2016

Reviewed on 03/28/2016

Product name: Mold Release Spray, Silicone (Hot Mounting)

(Contd. of page 7)

· **Additional toxicological information:**

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects:** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:** Contact waste processors for recycling information.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA** UN1950

· **UN proper shipping name**

· **DOT** Aerosols, flammable

· **IMDG** AEROSOLS

· **IATA** AEROSOLS, flammable

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2016

Reviewed on 03/28/2016

Product name: Mold Release Spray, Silicone (Hot Mounting)

(Contd. of page 8)

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
 · **Label** 2.1

· **Packing group**

· **DOT, IMDG, IATA** not regulated

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user**

Warning: Gases

· **Danger code (Kemler):**

-

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 75 kg
 On cargo aircraft only: 150 kg

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

US

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/28/2016

Reviewed on 03/28/2016

Product name: Mold Release Spray, Silicone (Hot Mounting)

(Contd. of page 9)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

100-41-4 ethylbenzene

· **TSCA (Toxic Substances Control Act):**

74-98-6 propane

8052-41-3 Stoddard solvent

1330-20-7 xylene

100-41-4 ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7 xylene

A4

100-41-4 ethylbenzene

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Kim Dermit

· **Date of preparation / last revision** 03/28/2016 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/28/2016

Reviewed on 03/28/2016

Product name: Mold Release Spray, Silicone (Hot Mounting)

(Contd. of page 10)

IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Gas 1: Flammable gases, Hazard Category 1
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
Press. Gas: Gases under pressure: Compressed gas
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Carc. 2: Carcinogenicity, Hazard Category 2
STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Asp. Tox. 1: Aspiration hazard, Hazard Category 1

US