

Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/03/2017 Reviewed on 03/03/2017

1 Identification

· Product name: Mold Release Spray (Cold Mounting)

· Part number: 200-10010

· Application of the substance / the mixture Releasing agent

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Allied High Tech Products Inc.

2376 East Pacifica Place

USA-RANCHO DOMINGUEZ, CA 90220

USA

info@alliedhightech.com

· Information department: Product safety department

· Emergency telephone number:

During normal opening times: +1 (310) 635-2466

Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



(Contd. on page 2)

Printing date 03/03/2017 Reviewed on 03/03/2017

Product name: Mold Release Spray (Cold Mounting)

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Acute 2 H401 Toxic to aquatic life.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02 GI

GHS07

GHS08 GHS09

- · Signal word Danger
- · Hazard-determining components of labeling:

Naphtha (petroleum), hydrotreated heavy

di-n-butyl ether

· Hazard statements

Extremely flammable aerosol. Pressurized container: May burst if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause genetic defects.

May cause cancer.

May cause respiratory irritation.

May be fatal if swallowed and enters airways.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not pierce or burn, even after use.

Do not spray on an open flame or other ignition source.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

(Contd. on page 3)

Printing date 03/03/2017 Reviewed on 03/03/2017

Product name: Mold Release Spray (Cold Mounting)

(Contd. of page 2)

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 0Reactivity = 3

· HMIS-ratings (scale 0 - 4)



Health = *1Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

64742-48-9	Naphtha (petroleum), hydrotreated heavy	50-100%
	🕸 Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304; Flam. Liq. 4, H227	
142-96-1	di-n-butyl ether	10-<25%
	🏈 Flam. Liq. 3, H226; 🗘 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	
74-98-6	propane	10-25%
	🔖 Flam. Gas 1, H220; Press. Gas, H280	
111-65-9	octane	2.5-<10%
	♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Irrit. 2, H315; STOT SE 3, H336	

· Non-hazardous Components:			
90622-56-3	Alkanes, C7-10-iso-	2.5-<10%	
	Proprietary Ingredient	2.5-<10%	

4 First-aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Headache

(Contd. on page 4)

Printing date 03/03/2017 Reviewed on 03/03/2017

Product name: Mold Release Spray (Cold Mounting)

(Contd. of page 3)

Dizziness

Unconsciousness

Nausea

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

<i>PAC-1:</i>		
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m.
142-96-1	di-n-butyl ether	2.6 ppm
74-98-6	propane	5500* ppn
111-65-9 octane		230 ppm
PAC-2:		
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m2
142-96-1	di-n-butyl ether	29 ppm
74-98-6	propane	17000** ppr
111-65-9 octane 3		385 ppm
<i>PAC-3:</i>		
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ²
142-96-1	di-n-butyl ether	170 ppm
74-98-6	propane	33000*** ррг
111-65-9	octane	5000** ppm

— U

Printing date 03/03/2017 Reviewed on 03/03/2017

Product name: Mold Release Spray (Cold Mounting)

(Contd. of page 4)

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store at temperatures not exceeding 48.8 °C.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

64742-48-9 Naphtha (petroleum), hydrotreated heavy

PEL Short-term value: 600 mg/m³, 100 ppm Long-term value: 300 mg/m³, 50 ppm

74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppm

REL Long-term value: 1800 mg/m³, 1000 ppm

TLV refer to Appendix F inTLVs&BEIs book; NIC-EX

111-65-9 octane

PEL Long-term value: 2350 mg/m³, 500 ppm

n-Octane only

REL Long-term value: 350 mg/m³, 75 ppm

Ceiling limit value: 1800* mg/m³, 385* ppm

*15 min

TLV Long-term value: 1401 mg/m³, 300 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

(Contd. on page 6)

Printing date 03/03/2017 Reviewed on 03/03/2017

Product name: Mold Release Spray (Cold Mounting)

(Contd. of page 5)

- · Breathing equipment: Use suitable respiratory protective device when high concentrations are present.
- · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

· Relative density



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and c	hemical properties
· General Information	
· Appearance:	
Form:	Aerosol
Color:	Colorless
· Odor: · Odor threshold:	Mild Not determined.
· Oaor inresnoia:	Not aeterminea.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	Not applicable, as aerosol.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	2412 hPa (1809 mm Hg)
Density:	Not determined.

Not determined.

(Contd. on page 7)

Printing date 03/03/2017 Reviewed on 03/03/2017

Product name: Mold Release Spray (Cold Mounting)

		(Contd. of page
· Vapor density	3.85	
· Specific gravity:	0.74	
· Evaporation rate at 20 °C (68 °F)	0.43 (Ether = 1)	
· Solubility in / Miscibility with		
Water:	Slightly soluble.	
· Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	37.1 %	
VOC content:	37.1 %	
	<i>371.4 g/l / 3.10 lb/gl</i>	
Solids content:	5.7 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Keep away from oxidising agents and acidic substances.

 $Keep\ away\ from\ alkaline\ solutions.$

Keep away from heat.

Keep away from open flames. - No smoking.

- $\cdot \textit{Incompatible materials:} \ \textit{No further relevant information available}.$
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Hydrocarbons Ammonia

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:					
· LD/LC50	· LD/LC50 values that are relevant for classification:				
ATE (Acu	ATE (Acute Toxicity Estimates)				
Dermal	LD50	5250 mg/kg (rab)			
Inhalative	LC50/4 h	4130 mg/l (rat)			
64742-48-	64742-48-9 Naphtha (petroleum), hydrotreated heavy				
Oral	LD50	>5000 mg/kg (rat)			
Dermal	LD50	>3000 mg/kg (rab)			
142-96-1	142-96-1 di-n-butyl ether				
Oral	LD50	7400 mg/kg (rat)			
	•	(Contd. on page 8)			

110

(Contd. of page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/03/2017 Reviewed on 03/03/2017

Product name: Mold Release Spray (Cold Mounting)

Dermal LD50 10000 mg/kg (rabbit)

111-65-9 octane

Inhalative LC50/4 h 118 mg/l (rat)

- · Primary chemical irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product can cause inheritable damage.

This material contains Hydrotreated heavy naphtha which may cause cancer - Carc 1B and may cause genetic defects - Muta 1B

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Contact waste processors for recycling information.

(Contd. on page 9)

Printing date 03/03/2017 Reviewed on 03/03/2017

Product name: Mold Release Spray (Cold Mounting)

(Contd. of page 8)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, IMDG, IATA	UN1950
UN proper shipping name	
DOT	Aerosols, flammable
IMDG	AEROSOLS (OCTANES), MARINE POLLUTANT
IATA	AEROSOLS, flammable
Transport hazard class(es)	
DOT	
CAMMARIE CAS	
2	
Class	2.1
Label	2.1
IMDG	
^	
\\\\\\\\\\	
2	
Class	2.1
Label	2.1
IATA	
^	
· Class	2.1
Label	2.1
Packing group	
DOT, IMDG, IATA	not regulated
Environmental hazards:	Product contains environmentally hazardous substances: octane
Marine pollutant:	Yes
_	Symbol (fish and tree)
Special precautions for user	Warning: Gases
Danger code (Kemler):	-
EMS Number:	F- D , S - U

Printing date 03/03/2017 Reviewed on 03/03/2017

Product name: Mold Release Spray (Cold Mounting)

	(Contd. of page
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litro
	Category A. For AEROSOLS with a capacity above 1 litro
	Category B. For WASTE AEROSOLS: Category C, Clear of livin quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litra
	Segregation as for class 9. Stow "separated from" class 1 except for
	division 1.4. For AEROSOLS with a capacity above 1 litr
	Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision
	of class 2.
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
Transport/Additional injormation.	
· DOT	
-	On passenger aircraft/rail: 75 kg
·DOT	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
·DOT	1 0 0
· DOT · Quantity limitations	1 0 0
· DOT · Quantity limitations · IMDG	On cargo aircraft only: 150 kg
· DOT · Quantity limitations · IMDG · Limited quantities (LQ)	On cargo aircraft only: 150 kg

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA	(Toxic	Substances	Control Act	١.
$I \cup C \cap A$	1 I UAIC	Substances	Common Act	

64742-48-9 Naphtha (petroleum), hydrotreated heavy

142-96-1 di-n-butyl ether

74-98-6 propane

111-65-9 octane

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 11)

Printing date 03/03/2017 Reviewed on 03/03/2017

Product name: Mold Release Spray (Cold Mounting)

(Contd. of page 10)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Kim Dermit
- · Date of preparation / last revision 03/03/2017 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

 $HMIS: \ Hazardous\ Materials\ Identification\ System\ (USA)$

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Gas 1: Flammable gases - Category 1

Flam. Aerosol 1: Aerosols - Category 1

Press. Gas: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Flam. Liq. 4: Flammable liquids - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1B: Carcinogenicity - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

(Contd. on page 12)

Printing date 03/03/2017 Reviewed on 03/03/2017

Product name: Mold Release Spray (Cold Mounting)

(Contd. of page 11)

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

T 10