

Safety Data Sheet acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/31/2016

1 Identification

- **Product name:** QuickMount Acrylic Liquid
- **Part number:**
140-10020
140-10035
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Allied High Tech Products Inc.
2376 East Pacifica Place
USA-RANCHO DOMINGUEZ, CA 90220
USA
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (310) 635-2466
Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

STOT RE 2 H373 May cause damage to the lung, the kidneys, the liver and the heart through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/31/2016

Product name: QuickMount Acrylic Liquid

(Contd. of page 1)

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

methyl methacrylate

N,N-dimethyl-p-toluidine

1,3-Butanediol dimethacrylate

· **Hazard statements**

Flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

May cause damage to the lung, the kidneys, the liver and the heart through prolonged or repeated exposure.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO₂, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 2

Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/31/2016

Product name: QuickMount Acrylic Liquid

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = 1
FIRE	2	Fire = 2
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Hazardous Components:

80-62-6	methyl methacrylate ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
1189-08-8	1,3-Butanediol dimethacrylate ⚠ Eye Irrit. 2A, H319; STOT SE 3, H335	2.5-<10%
99-97-8	N,N-dimethyl-p-toluidine ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT RE 2, H373; Flam. Liq. 4, H227; Aquatic Chronic 3, H412	0.1-≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
Headache
Coughing
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/31/2016

Product name: QuickMount Acrylic Liquid

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Do not allow to enter sewers/ surface or ground water.
Prevent seepage into sewage system, workpits and cellars.
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

80-62-6 methyl methacrylate

PEL	Long-term value: 410 mg/m ³ , 100 ppm
-----	--

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/31/2016

Product name: QuickMount Acrylic Liquid

(Contd. of page 4)

REL	Long-term value: 410 mg/m ³ , 100 ppm
TLV	Short-term value: 410 mg/m ³ , 100 ppm Long-term value: 205 mg/m ³ , 50 ppm DSEN
99-97-8 N,N-dimethyl-p-toluidine	
WEEL	Long-term value: 0.5 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Nitrile rubber, NBR

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Clear

· **Odor:** Acrylic

· **Odor threshold:** 0.049 ppm

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: -48 °C (-54 °F)

Boiling point/Boiling range: 101 °C (214 °F)

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/31/2016

Product name: QuickMount Acrylic Liquid

(Contd. of page 5)

· Flash point:	55 °C (131 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	430 °C (806 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapor pressure at 20 °C (68 °F):	39 hPa (29 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density at 20 °C (68 °F)	3.5 g/cm ³ (29.208 lbs/gal)
· Specific gravity:	0.936 (water = 1)
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Partly soluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
VOC content:	0.0 g/l / 0.00 lb/gl
Solids content:	7.6 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
 Keep away from oxidising agents and acidic substances.
 Keep away from heat.
 Keep away from open flames. - No smoking.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/31/2016

Product name: QuickMount Acrylic Liquid

(Contd. of page 6)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	86623 mg/kg (rat)
Dermal	LD50	4091 mg/kg
Inhalative	LC50/4 h	15.7 mg/l (rat)

80-62-6 methyl methacrylate

Oral	LD50	7872 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)
Inhalative	LC50/4 h	18 mg/l (rat)

99-97-8 N,N-dimethyl-p-toluidine

Oral	LD50	1650 mg/kg (rat)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	1.4 mg/l (rat)

- **Primary chemical irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

80-62-6	methyl methacrylate	3
---------	---------------------	---

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

80-62-6 methyl methacrylate

EC50 (96 h)	170 mg/l (pseudokirchneriella subcapitata)
EC50 (48 h)	69 mg/l (daphnia)
LC50 (96 h)	79 mg/l (oncorhynchus mykiss)

- **Persistence and degradability** No further relevant information available.
 - **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
 - **Additional ecological information:**
 - **General notes:**
- Water hazard class 1 (Self-assessment): slightly hazardous for water

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/31/2016

Product name: QuickMount Acrylic Liquid



(Contd. of page 7)

- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Contact waste processors for recycling information.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---------------------------------------|---|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1247 |
| · UN proper shipping name | |
| · DOT | Methyl methacrylate monomer, stabilized |
| · IMDG, IATA | METHYL METHACRYLATE MONOMER, STABILIZED |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| | |
| · IMDG, IATA | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | |
| · DOT, IMDG, IATA | II |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| · Danger code (Kemler): | 30 |
| · EMS Number: | F-E,S-D |
| · Stowage Category | B |
| · Stowage Code | SW2 Clear of living quarters. |

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/31/2016

Product name: QuickMount Acrylic Liquid

(Contd. of page 8)

- | | |
|--|---|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L |
| <hr style="border-top: 1px dashed black;"/> | |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED, 3, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 | methyl methacrylate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65
· Chemicals known to cause cancer:

99-97-8 | N,N-dimethyl-p-toluidine

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories
· EPA (Environmental Protection Agency)

80-62-6 | methyl methacrylate

E, NL

· TLV (Threshold Limit Value established by ACGIH)

80-62-6 | methyl methacrylate

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/31/2016

Product name: QuickMount Acrylic Liquid

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Kim Dermit
- **Date of preparation / last revision** 03/31/2016 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

1 Identification

- **Product name:** QuickMount Acrylic Powder
- **Part number:**
140-10020
140-10025
- **Application of the substance / the mixture** Acrylic resin
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Allied High Tech Products Inc.
2376 East Pacifica Place
USA-RANCHO DOMINGUEZ, CA 90220
USA
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (310) 635-2466
Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

- **Classification of the substance or mixture**



Flam. Sol. 1 H228 Flammable solid.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Danger

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

Product name: QuickMount Acrylic Powder

(Contd. of page 1)

· Hazard-determining components of labeling:

dibenzoyl peroxide

· Hazard statements

Flammable solid.

May cause an allergic skin reaction.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Contaminated work clothing must not be allowed out of the workplace.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO₂, powder or water spray.

IF ON SKIN: Wash with plenty of water.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:
· NFPA ratings (scale 0 - 4)


Health = 0

Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)


Health = 0

Fire = 1

Reactivity = 0

· Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures
· Description: Mixture of the substances listed below with nonhazardous additions.

· Hazardous Components:

9011-14-7	Methyl methacrylate polymer Combustible Dust	50-100%
94-36-0	dibenzoyl peroxide ⚠️ ⚠️ Org. Perox. B, H241; ⚠️ Eye Irrit. 2A, H319; Skin Sens. 1, H317	2.5-<10%

· Non-hazardous Components:

7732-18-5	water, distilled, conductivity or of similar purity	0.1-≤2.5%
-----------	---	-----------

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

Product name: QuickMount Acrylic Powder

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

Product name: QuickMount Acrylic Powder

(Contd. of page 3)

- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

9011-14-7 Methyl methacrylate polymer

PEL	Long-term value: 410 mg/m ³
TLV	Long-term value: 205 mg/m ³

94-36-0 dibenzoyl peroxide

PEL	Long-term value: 5 mg/m ³
REL	Long-term value: 5 mg/m ³
TLV	Long-term value: 5 mg/m ³

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
- **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.
- **Protection of hands:**
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Not required.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
Form: Powder

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

Product name: QuickMount Acrylic Powder

(Contd. of page 4)

Color:	White
· Odor:	methacrylate-like
· Odor threshold:	Not determined.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	150 °C (302 °F)
Boiling point/Boiling range:	Undetermined.
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not applicable.
· Density at 20 °C (68 °F):	1.1999 g/cm ³ (10.013 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not applicable.
· Specific gravity:	1.18
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Organic solvents:	0.0 %
Water:	2.0 %
VOC content:	0.0 g/l / 0.00 lb/gl
Solids content:	98.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

Product name: QuickMount Acrylic Powder

(Contd. of page 5)

- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Methacrylate monomers
Benzene
Benzoic acid
- **Additional information:** May decompose if heated to temperatures above 200 C.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary chemical irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:** Abrasive eye irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

9011-14-7	Methyl methacrylate polymer	3
94-36-0	dibenzoyl peroxide	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Contact waste processors for recycling information.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

Product name: QuickMount Acrylic Powder

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|-----------------|
| · UN-Number | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · DOT, ADN, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · DOT, IMDG, IATA | not regulated |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

94-36-0 dibenzoyl peroxide

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

Product name: QuickMount Acrylic Powder

(Contd. of page 7)

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

94-36-0 dibenzoyl peroxide

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Kim Dermitt

· **Date of preparation / last revision** 03/29/2016 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

LC50: Lethal concentration, 50 percent

BEI: Biological Exposure Limit

Flam. Sol. 1: Flammable solids, Hazard Category 1

Org. Perox. B: Organic Peroxides, Type B

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1