

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

**1 Identification**

- **Product name:** QuickSet Acrylic Liquid
- **Part number:**  
185-10000, -10015  
185-10025, -10035, -10036, -10045
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Allied High Tech Products Inc.  
2376 East Pacifica Place  
USA-RANCHO DOMINGUEZ, CA 90220  
USA  
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (310) 635-2466  
Chemtrec: +1 (202) 483-7616

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS09 Environment

Aquatic Acute 1 H400 Very toxic to aquatic life.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2A H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 1)

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02    GHS07    GHS09

· **Signal word** Warning

· **Hazard-determining components of labeling:**

isobutyl methacrylate

mequinol

· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

Very toxic to aquatic life.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Avoid release to the environment.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	2	Fire = 2
REACTIVITY	2	Reactivity = 2

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Hazardous Components:**

97-86-9	isobutyl methacrylate ⚠ Flam. Liq. 3, H226; ⚠ Aquatic Acute 1, H400; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
150-76-5	mequinol ⚠ Acute Tox. 4, H302; Eye Irrit. 2A, H319; Skin Sens. 1, H317	≤10%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** Dizziness
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 4)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 3)

- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Do not allow to enter sewers/ surface or ground water.  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Store at temperatures not exceeding 25 °C.  
Keep receptacle tightly sealed.  
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

(Contd. on page 5)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 4)

### 150-76-5 mequinol

REL Long-term value: 5 mg/m<sup>3</sup>TLV Long-term value: 5 mg/m<sup>3</sup>

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves** Butyl rubber, BR
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

Form:	Liquid
Color:	Clear
· Odor:	Characteristic
· Odor threshold:	Not determined.

· pH-value: Not determined.

#### · Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	155 °C (311 °F)

· Flash point: 49 °C (120 °F) (closed cup)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 390 °C (734 °F)

· Decomposition temperature: Not determined.

(Contd. on page 6)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 5)

· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1 Vol %
<b>Upper:</b>	8 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	4 hPa (3 mm Hg)
· <b>Density:</b>	Not determined.
· <b>Relative density</b>	Not determined.
· <b>Vapor density at 16 °C (61 °F)</b>	4.91 (Air = 1)
· <b>Specific gravity at 15.5 °C (60 °F):</b>	0.901
· <b>Evaporation rate</b>	0.5
· <b>Solubility in / Miscibility with Water:</b>	0.47 g/l
· <b>Partition coefficient (n-octanol/water):</b>	2.95 log POW
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
<b>VOC content:</b>	0.0 g/l / 0.00 lb/gl
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Danger of polymerization.
- **Conditions to avoid**  
Protect from sunlight.  
Keep away from heat.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**97-86-9 isobutyl methacrylate**

Oral	LD50	11990 mg/kg (mouse)
------	------	---------------------

- **Primary chemical irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 6)

· **Additional toxicological information:**

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

EC50 (48 h) 29 mg/l (daphnia)

LC50 (96 h) 20 mg/l (rainbow trout)

· **Persistence and degradability** Easily biodegradable

· **Behavior in environmental systems:**

· **Bioaccumulative potential** May be accumulated in organism

· **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Very toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Very toxic for aquatic organisms

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:** Contact waste processors for recycling information.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UN2283

· **UN proper shipping name**

· **DOT**

· **IMDG**

Isobutyl methacrylate, stabilized mixture

ISOBUTYL METHACRYLATE, STABILIZED mixture, MARINE POLLUTANT

(Contd. on page 8)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 7)

· **IATA** *ISOBUTYL METHACRYLATE, STABILIZED mixture*

· **Transport hazard class(es)**· **DOT**

· **Class** 3 Flammable liquids  
 · **Label** 3

· **IMDG**

· **Class** 3 Flammable liquids  
 · **Label** 3

· **IATA**

· **Class** 3 Flammable liquids  
 · **Label** 3

· **Packing group**· **DOT, IMDG, IATA** III

· **Environmental hazards:** *Product contains environmentally hazardous substances: isobutyl methacrylate*

· **Marine pollutant:** *Yes*  
*Symbol (fish and tree)*

· **Special precautions for user** *Warning: Flammable liquids*· **Danger code (Kemler):** 30· **EMS Number:** F-E,S-D· **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** *Not applicable.*

· **Transport/Additional information:**· **DOT**

· **Quantity limitations** *On passenger aircraft/rail: 60 L*  
*On cargo aircraft only: 220 L*

· **IMDG**· **Limited quantities (LQ)** 5L

· **Excepted quantities (EQ)** *Code: E1*  
*Maximum net quantity per inner packaging: 30 ml*  
*Maximum net quantity per outer packaging: 1000 ml*

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 8)

<ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>	<p>UN 2283 ISOBUTYL METHACRYLATE, STABILIZED MIXTURE, ENVIRONMENTALLY HAZARDOUS, 3, III, ENVIRONMENTALLY HAZARDOUS</p>
---	--

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Environment protection department.

- **Contact:** Kim Dermit

- **Date of preparation / last revision** 03/29/2016 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 10)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 03/29/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 9)

*EINECS: European Inventory of Existing Commercial Chemical Substances*  
*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*NFPA: National Fire Protection Association (USA)*  
*HMIS: Hazardous Materials Identification System (USA)*  
*VOC: Volatile Organic Compounds (USA, EU)*  
*LC50: Lethal concentration, 50 percent*  
*LD50: Lethal dose, 50 percent*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*vPvB: very Persistent and very Bioaccumulative*  
*NIOSH: National Institute for Occupational Safety*  
*OSHA: Occupational Safety & Health*  
*TLV: Threshold Limit Value*  
*PEL: Permissible Exposure Limit*  
*REL: Recommended Exposure Limit*  
*BEI: Biological Exposure Limit*  
*Flam. Liq. 3: Flammable liquids, Hazard Category 3*  
*Acute Tox. 4: Acute toxicity, Hazard Category 4*  
*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*  
*Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A*  
*Skin Sens. 1: Sensitisation - Skin, Hazard Category 1*  
*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*  
*Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1*

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/29/2016

**1 Identification**

- **Product name:** QuickSet Acrylic Powder
- **Part number:**  
185-10000, -10015  
185-10005, -10020, -10030, -10040, -10041
- **Application of the substance / the mixture** Acrylic resin
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Allied High Tech Products Inc.  
2376 East Pacifica Place  
USA-RANCHO DOMINGUEZ, CA 90220  
USA  
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (310) 635-2466  
Chemtrec: +1 (202) 483-7616

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



Skin Sens. 1 H317 May cause an allergic skin reaction.

Eye Irrit. 2B H320 Causes eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Warning
- **Hazard-determining components of labeling:**  
dibenzoyl peroxide

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Powder**

(Contd. of page 1)

**· Hazard statements**

Causes eye irritation.  
May cause an allergic skin reaction.

**· Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray  
Wear protective gloves.  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Specific treatment (see on this label).  
Wash contaminated clothing before reuse.  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
IF ON SKIN: Wash with plenty of water.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Classification system:**
**· NFPA ratings (scale 0 - 4)**


Health = 1  
Fire = 1  
Reactivity = 0

**· HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

**· Other hazards**
**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Description:** Mixture of the substances listed below with nonhazardous additions.

**· Hazardous Components:**

9003-42-3	Poly(ethyl methacrylate) Eye Irrit. 2B, H320	50-100%
94-36-0	dibenzoyl peroxide ⚠️ Org. Perox. B, H241; ⚠️ Eye Irrit. 2A, H319; Skin Sens. 1, H317	1-≤2.5%

### 4 First-aid measures

**· Description of first aid measures**
**· After inhalation:**

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**· After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Powder**

(Contd. of page 2)

- **After swallowing:** *If symptoms persist consult doctor.*
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
Headache  
Nausea
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** *Use fire fighting measures that suit the environment.*
- **Special hazards arising from the substance or mixture** *No further relevant information available.*
- **Advice for firefighters**
- **Protective equipment:** *No special measures required.*

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** *Not required.*
- **Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**  
*Pick up mechanically.*  
*Dispose contaminated material as waste according to item 13.*  
*Ensure adequate ventilation.*
- **Reference to other sections**  
*See Section 7 for information on safe handling.*  
*See Section 8 for information on personal protection equipment.*  
*See Section 13 for disposal information.*

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** *No special precautions are necessary if used correctly.*
- **Information about protection against explosions and fires:** *No special measures required.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *Store at temperatures not exceeding 35 °C.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:**  
*Keep receptacle tightly sealed.*  
*Store receptacle in a well ventilated area.*
- **Specific end use(s)** *No further relevant information available.*

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Powder**

(Contd. of page 3)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

**94-36-0 dibenzoyl peroxide**

PEL Long-term value: 5 mg/m<sup>3</sup>

REL Long-term value: 5 mg/m<sup>3</sup>

TLV Long-term value: 5 mg/m<sup>3</sup>

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.

- **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Powder

**Color:** White

· **Odor:** Light

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Powder**

(Contd. of page 4)

· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	Not applicable.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	Undetermined.
· <b>Flash point:</b>	304 °C (579 °F)
· <b>Flammability (solid, gaseous):</b>	Not determined.
· <b>Ignition temperature:</b>	
<b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Vapor pressure:</b>	Not applicable.
· <b>Density:</b>	Not determined.
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not applicable.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with Water:</b>	Insoluble.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not applicable.
<b>Kinematic:</b>	Not applicable.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
<b>VOC content:</b>	0.0 g/l / 0.00 lb/gl
<b>Solids content:</b>	100.0 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**  
     Temperatures above 240 °C (464 °F)  
     Keep away from oxidising agents and acidic substances.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
     Methacrylate monomer vapors  
     Carbon monoxide and carbon dioxide

(Contd. on page 6)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Powder**

(Contd. of page 5)

· **Additional information:** Hazardous products form when material is burned.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary chemical irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:** Abrasive eye irritant
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

94-36-0 dibenzoyl peroxide

3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
- Water hazard class 1 (Self-assessment): slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Contact waste processors for recycling information.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

US

(Contd. on page 7)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Powder**

(Contd. of page 6)

## 14 Transport information

<b>· UN-Number</b>	
<b>· DOT, ADN, IMDG, IATA</b>	<i>not regulated</i>
<b>· UN proper shipping name</b>	
<b>· DOT, ADN, IMDG, IATA</b>	<i>not regulated</i>
<b>· Transport hazard class(es)</b>	
<b>· DOT, ADN, IMDG, IATA</b>	
<b>· Class</b>	<i>not regulated</i>
<b>· Packing group</b>	
<b>· DOT, IMDG, IATA</b>	<i>not regulated</i>
<b>· Environmental hazards:</b>	
<b>· Marine pollutant:</b>	<i>No</i>
<b>· Special precautions for user</b>	<i>Not applicable.</i>
<b>· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	<i>Not applicable.</i>
<b>· UN "Model Regulation":</b>	<i>not regulated</i>

## 15 Regulatory information

<b>· Safety, health and environmental regulations/legislation specific for the substance or mixture</b>	
<b>· Sara</b>	
<b>· Section 355 (extremely hazardous substances):</b>	
<i>None of the ingredients is listed.</i>	
<b>· Section 313 (Specific toxic chemical listings):</b>	
94-36-0	<i>dibenzoyl peroxide</i>
<b>· TSCA (Toxic Substances Control Act):</b>	
<i>All ingredients are listed.</i>	
<b>· Proposition 65</b>	
<b>· Chemicals known to cause cancer:</b>	
<i>None of the ingredients is listed.</i>	
<b>· Chemicals known to cause reproductive toxicity for females:</b>	
<i>None of the ingredients is listed.</i>	
<b>· Chemicals known to cause reproductive toxicity for males:</b>	
<i>None of the ingredients is listed.</i>	
<b>· Chemicals known to cause developmental toxicity:</b>	
<i>None of the ingredients is listed.</i>	
<b>· Carcinogenic categories</b>	
<b>· EPA (Environmental Protection Agency)</b>	
<i>None of the ingredients is listed.</i>	
<b>· TLV (Threshold Limit Value established by ACGIH)</b>	
94-36-0	<i>dibenzoyl peroxide</i>

A4

(Contd. on page 8)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/31/2016

Reviewed on 03/29/2016

**Product name: QuickSet Acrylic Powder**

(Contd. of page 7)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Environment protection department.

· **Contact:** Kim Dermit

· **Date of preparation / last revision** 03/31/2016 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

LC50: Lethal concentration, 50 percent

BEI: Biological Exposure Limit

Org. Perox. B: Organic peroxides – Type B

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

Skin Sens. 1: Skin sensitisation – Category 1